



Queensland

*Coastal Protection and Management Act 1995*

# Coastal Protection and Management Regulation 2003

Reprinted as in force on 18 December 2009

Reprint No. 3A

This reprint is prepared by  
the Office of the Queensland Parliamentary Counsel  
Warning—This reprint is not an authorised copy

# Information about this reprint

This regulation is reprinted as at 18 December 2009. The reprint shows the law as amended by all amendments that commenced on or before that day (Reprints Act 1992 s 5(c)).

The reprint includes a reference to the law by which each amendment was made—see list of legislation and list of annotations in endnotes. Also see list of legislation for any uncommenced amendments.

This page is specific to this reprint. See previous reprints for information about earlier changes made under the Reprints Act 1992. A table of reprints is included in the endnotes.

**Also see endnotes for information about—**

- **when provisions commenced**
- **editorial changes made in earlier reprints.**

## Spelling

The spelling of certain words or phrases may be inconsistent in this reprint or with other reprints because of changes made in various editions of the Macquarie Dictionary (for example, in the dictionary, ‘lodgement’ has replaced ‘lodgment’). Variations of spelling will be updated in the next authorised reprint.

## Dates shown on reprints

**Reprints dated at last amendment** All reprints produced on or after 1 July 2002, authorised (that is, hard copy) and unauthorised (that is, electronic), are dated as at the last date of amendment. Previously reprints were dated as at the date of publication. If an authorised reprint is dated earlier than an unauthorised version published before 1 July 2002, it means the legislation was not further amended and the reprint date is the commencement of the last amendment.

If the date of an authorised reprint is the same as the date shown for an unauthorised version previously published, it merely means that the unauthorised version was published before the authorised version. Also, any revised edition of the previously published unauthorised version will have the same date as that version.

**Replacement reprint date** If the date of an authorised reprint is the same as the date shown on another authorised reprint it means that one is the replacement of the other.



Queensland

# Coastal Protection and Management Regulation 2003

## Contents

---

		Page
<b>Part 1</b>	<b>Preliminary</b>	
1	Short title . . . . .	3
2	Commencement . . . . .	3
3	Definitions . . . . .	3
<b>Part 2</b>	<b>Coastal building lines</b>	
4	Fixing coastal building lines—Act, s 66 . . . . .	3
<b>Part 3</b>	<b>Fees and royalties</b>	
<b>Division 1</b>	<b>Fees</b>	
5	Fees for assessment of development application . . . . .	4
6	Fees for allocations and dredge management plans . . . . .	5
<b>Division 2</b>	<b>Royalties</b>	
7	Rate of royalty—Act, s 102 . . . . .	5
8	When royalty payable—Act, s 102 . . . . .	5
9	Royalty not payable for particular transport-related matters . . . . .	6
10	Application for waiver of royalty . . . . .	7
11	When waiver application may be made . . . . .	7
12	When royalty must be waived . . . . .	8
13	Refund of royalty waived . . . . .	8
<b>Part 4</b>	<b>Prescribed tidal work</b>	
14	Work that is prescribed tidal work . . . . .	8
15	Work that is not prescribed tidal work . . . . .	9
16	Code for IDAS for prescribed tidal work . . . . .	10
<b>Schedule 1</b>	<b>Coastal building lines</b> . . . . .	11
<b>Schedule 2</b>	<b>Fees for assessment of development applications</b> . . . . .	12
<b>Schedule 3</b>	<b>Fees for allocations and dredge management plans</b> . . . . .	15
<b>Schedule 4</b>	<b>Royalty payable for removal of quarry material</b> . . . . .	16

Contents

---

<b>Schedule 4A</b>	<b>IDAS code for development applications for prescribed tidal work</b> .....	17
<b>Part 1</b>	<b>Preliminary</b>	
1	Application of code .....	17
2	Purpose of code .....	17
3	Definitions .....	18
4	When lot connected to prescribed tidal work .....	23
5	References to s 6(2) solution in probable solution .....	23
<b>Part 2</b>	<b>Compliance with code</b>	
6	How to comply with code .....	24
7	Relationship between particular specific outcomes and probable solutions .....	24
<b>Part 3</b>	<b>Specific outcomes and probable solutions</b>	
<b>Schedule 5</b>	<b>Dictionary</b> .....	57
 <b>Endnotes</b>		
1	Index to endnotes .....	58
2	Date to which amendments incorporated .....	58
3	Key .....	58
4	Table of reprints .....	59
5	List of legislation .....	59
6	List of annotations .....	61

---

# Coastal Protection and Management Regulation 2003

[as amended by all amendments that commenced on or before 18 December 2009]

## Part 1 Preliminary

### 1 Short title

This regulation may be cited as the *Coastal Protection and Management Regulation 2003*.

### 2 Commencement

This regulation commences on 20 October 2003.

### 3 Definitions

The dictionary in schedule 5 defines particular words used in this regulation.

## Part 2 Coastal building lines

### 4 Fixing coastal building lines—Act, s 66

- (1) A line shown as a set-back line on a plan stated in schedule 1, column 3, is the coastal building line for the relevant coastal management district for the plan.

*Editor's note—*

See also the *Coastal Protection and Management (Coastal Management Districts) Regulation 2003*, schedule.

[s 5]

---

- (2) The chief executive must—
  - (a) keep each plan stated in schedule 1, column 3, available for inspection, free of charge, by members of the public; and
  - (b) allow a person to take, free of charge, a copy of an extract from the plan showing a set-back line.
- (3) In this section—

*relevant coastal management district*, for a plan stated in schedule 1, column 3, means the coastal management district—

  - (a) stated opposite the plan in schedule 1, column 2; and
  - (b) situated in the local government area stated opposite the plan in schedule 1, column 1.

## **Part 3 Fees and royalties**

### **Division 1 Fees**

#### **5 Fees for assessment of development application**

- (1) The fees payable for assessment of a development application under chapter 2, part 6 of the Act are stated in—
  - (a) for an application in connection with the construction of an artificial waterway—schedule 2, part 1; and
  - (b) for an application other than in connection with the construction of an artificial waterway—schedule 2, part 2.
- (2) However, if the applicant has a preliminary approval for the development under the development application, the fee payable for assessment of the application is—

- 
- (a) for an application mentioned in schedule 2, part 1, item 1 or schedule 2, part 2, item 1 or 2(a) or (b)—nil; or
  - (b) for an application mentioned in schedule 2, part 1, item 2—the sum of the following—
    - (i) the fee payable under schedule 2, part 1, item 2(b), less the fee paid for operational works in relation to the preliminary approval;
    - (ii) the fee payable under schedule 2, part 1, item 2(c), less any fee paid for reconfiguring a lot in relation to the preliminary approval; or
  - (c) for an application mentioned in schedule 2, part 2, item 2(c) or (d)—the fee payable under that item, less any fee paid for operational works in relation to the preliminary approval; or
  - (d) for an application mentioned in schedule 2, part 2, item 3—the fee payable under schedule 2, part 2, item 3, less any fee paid for reconfiguring a lot in relation to the preliminary approval.

## **6 Fees for allocations and dredge management plans**

The fees payable under the Act in relation to an allocation or a dredge management plan are stated in schedule 3.

## **Division 2 Royalties**

### **7 Rate of royalty—Act, s 102**

For section 102(1) of the Act, the rate at which royalty is payable is stated in schedule 4.

### **8 When royalty payable—Act, s 102**

For section 102(1) of the Act, royalty is payable—

[s 9]

---

- (a) for quarry material removed under an allocation notice—when a notice mentioned in section 80(2) of the Act is given to the chief executive for the removal; or
- (b) for quarry material removed under an approved dredge management plan—when information is given, under the plan, to the chief executive about the quantity of quarry material removed.

## **9 Royalty not payable for particular transport-related matters**

- (1) No royalty is payable for quarry material removed by any of the following persons if the conditions stated in subsection (2) are satisfied in relation to the removal—
  - (a) the chief executive of the department in which the *Transport Infrastructure Act 1994*, to the extent it relates to transport infrastructure other than roads, is administered;
  - (b) a person who manages a public marine facility;
  - (c) a person who is removing the quarry material for a person mentioned in paragraph (a) or (b).
- (2) For subsection (1), the conditions are—
  - (a) the person removes the material to develop, maintain or improve navigational channels; and
  - (b) the person disposes of the material on land; and
  - (c) the material is to be used for—
    - (i) beach nourishment, filling or reclamation purposes; or
    - (ii) another purpose that does not involve the sale of any of the material.
- (3) No royalty is payable by a port authority for quarry material removed—
  - (a) to maintain or improve navigational channels or navigation in its port if the material is disposed of—



- (i) in an area associated with port activities and approved by the Minister of the department in which the *Transport Infrastructure Act 1994* is administered; and
  - (ii) under relevant statutory environmental controls; or
- (b) to reclaim land that is, or is proposed to be, strategic port land under the *Transport Infrastructure Act 1994*.

## 10 Application for waiver of royalty

- (1) A person may apply to the chief executive (a ***waiver application***) for the chief executive to waive, completely or partly, payment of a royalty by the person if the quarry material removed under an allocation notice or an approved dredge management plan—
- (a) is used, or to be used, for beach nourishment in relation to which the person has a development approval; or
  - (b) is mostly mud, silt, or clay disposed of, or to be disposed of, on land for filling or reclamation purposes; or
  - (c) is placed, or to be placed, on land to avoid an adverse effect, or a potential adverse effect, on the environment.
- (2) The waiver application must be accompanied by enough evidence to support the person's eligibility to make the application under subsection (1)(a), (b) or (c).

## 11 When waiver application may be made

- (1) A person may make a waiver application only—
- (a) if the royalty is payable for quarry material removed under an allocation notice—when the person applies for the allocation or the person gives the chief executive a notice mentioned in section 80(2) of the Act for the removal; or
  - (b) if the royalty is payable for quarry material removed under an approved dredge management plan—when the person applies for approval of the plan or the person

[s 12]

---

gives information, under the plan, to the chief executive about the quantity of material removed.

- (2) Also, a person may make a waiver application only if there is no outstanding amount of royalty payable by the person when the application is made.

## **12 When royalty must be waived**

The chief executive must waive payment of an amount of royalty by a person for quarry material removed under an allocation notice or an approved dredge management plan if the chief executive is satisfied the quarry material—

- (a) is used, or to be used, for beach nourishment in relation to which the person has a development approval; or
- (b) is mostly mud, silt, or clay disposed of, or to be disposed of, on land for filling or reclamation purposes; or
- (c) is placed, or to be placed, on land to avoid an adverse effect, or a potential adverse effect, on the environment.

## **13 Refund of royalty waived**

If, for a waiver application, the chief executive waives payment of an amount of royalty under section 12 and the applicant has paid the royalty, the chief executive must, within 20 business days after receiving the application, repay the amount of the royalty waived.

# **Part 4 Prescribed tidal work**

## **14 Work that is prescribed tidal work**

- (1) For this regulation and the Planning Act, subject to section 15, the following work is prescribed tidal work if it is completely or partly within a local government tidal area—

- (a) work that is completely tidal work;
  - (b) work consisting of—
    - (i) tidal work; and
    - (ii) a part that is not tidal work if the part is an integral part of the work.
- (2) In this section—  
*tidal area*, for a local government, see the Planning Act, schedule 3.

## 15 Work that is not prescribed tidal work

- (1) The following work is not prescribed tidal work for this regulation or the Planning Act—
- (a) tidal work for a new or existing structure used for the operation of—
    - (i) a port authority; or
    - (ii) a public marine facility constructed by or for Queensland Transport or a port authority;
  - (b) tidal work for any of the following—
    - (i) creating or changing the configuration or characteristics of a navigational channel;
    - (ii) an inlet or outlet for development for aquaculture if the development is carried out on land and is made self-assessable under the local government's planning scheme or is development requiring compliance assessment under the Planning Act;
  - (c) tidal work the subject of—
    - (i) a deemed approval; or
    - (ii) a development approval given under the repealed *Integrated Planning Act 1997* on or before the day this section commenced; or
    - (iii) a development application made under the repealed *Integrated Planning Act 1997* but not

[s 16]

---

decided on or before the day this section commenced.

(2) In this section—

*aquaculture* see the *Fisheries Act 1994*, schedule.

*navigational channel* means a channel marked by aids to navigation built, erected or placed in tidal water under the *Transport Operations (Marine Safety) Act 1994*.

*Queensland Transport* means the department in which the *Transport Operations (Marine Safety) Act 1994* is administered.

## **16 Code for IDAS for prescribed tidal work**

(1) The code for IDAS for development applications for prescribed tidal work is in schedule 4A.

(2) In this section—

*IDAS* means the system detailed in the Planning Act, chapter 6, for integrating State and local government assessment and approval processes for development.

---

**Schedule 1 Coastal building lines**

section 4

<b>Local government area</b>	<b>Coastal management district</b>	<b>Plan number</b>
City of Hervey Bay	16	SC3354 and SC3355
City of Maryborough	16	SC3356
Shire of Bowen	18	SC3357, SC3359 and SC3361
Shire of Noosa	8	SC3331 to SC3338 and SC3339A to SC3342

## Schedule 2 Fees for assessment of development applications

section 5

### Part 1 Applications in connection with the construction of an artificial waterway

	\$
1 Application for a material change of use of premises completely or partly within a coastal management district .....	17 606.00
2 Application for carrying out operational work and reconfiguring a lot completely or partly within a coastal management district—	
(a) if there is no application for a material change of use in relation to the development—for the application .....	17 606.00
(b) for the operational work—for each metre, or part of a metre, of land fronting the proposed work .....	12.20
(c) for the reconfiguring—	
(i) 1 or 2 lots after reconfiguring .....	585.00
(ii) 3 lots after reconfiguring .....	878.00
(iii) 4 lots after reconfiguring .....	1 172.00
(iv) 5 lots after reconfiguring .....	1 466.00
(v) more than 5 lots after reconfiguring .....	1 758.00

## Part 2 Applications other than in connection with the construction of an artificial waterway

	\$
1 Application for a material change of use of premises completely or partly within a coastal management district .....	1 758.00
2 Application for carrying out operational work that is tidal works, or works completely or partly within a coastal management district—	
(a) for coastal management purposes involving beach nourishment, dune fencing, revegetation of dunal areas with endemic native plants, or stinger net enclosures. ....	nil
(b) for a purpose directly related to the provision of life saving or rescue services by a volunteer community organisation .....	nil
(c) for a private purpose—	
(i) if the application relates to only 1 residence .....	234.60
(ii) if the application relates to 2 or more residences and the operational work does not include a structure used for berthing a vessel .....	234.60
(iii) if the application relates to 2 or more residences and the operational work includes 1 or more structures used for berthing a vessel—for each structure used for berthing a vessel. ....	234.60
(d) for another purpose and the value of the completed works is—	
(i) \$10000 or less .....	608.00
(ii) more than \$10000 but not more than \$25000 .....	1 077.00

Schedule 2

	\$
(iii) more than \$25000 but not more than \$50000.....	1 288.00
(iv) more than \$50000 but not more than \$100000.....	2 146.00
(v) more than \$100000 but not more than \$250000.....	2 580.00
(vi) more than \$250000 but not more than \$500000.....	3 402.00
(vii) more than \$500000 but not more than \$1 million.....	5 983.00
(viii) more than \$1 million but not more than \$2.5 million.....	7 275.00
(ix) more than \$2.5 million but not more than \$5 million.....	12 206.00
(x) more than \$5 million but not more than \$10 million.....	14 084.00
(xi) more than \$10 million but not more than \$25 million.....	19 952.00
(xii) more than \$25 million.....	23 474.00
3 Application for reconfiguring a lot, completely or partly within a coastal management district—	
(a) 1 or 2 lots after reconfiguring.....	585.00
(b) 3 lots after reconfiguring.....	878.00
(c) 4 lots after reconfiguring.....	1 172.00
(d) 5 lots after reconfiguring.....	1 466.00
(e) more than 5 lots after reconfiguring.....	1 758.00



---

## Schedule 3 Fees for allocations and dredge management plans

section 6

\$

1	Application for an allocation or an approval of a dredge management plan (Act, s 73(2)(b) or 91(2)(b)), allowing the removal of—	
	(a) not more than 10000m <sup>3</sup> of quarry material . . . .	187.60
	(b) more than 10000m <sup>3</sup> of quarry material . . . . .	560.00
2	Application to transfer all or part of an allocation or an approved dredge management plan (Act, s 82(2)(c) or 95(2)(b)), allowing the removal of—	
	(a) not more than 10000m <sup>3</sup> of quarry material . . . .	58.65
	(b) more than 10000m <sup>3</sup> of quarry material . . . . .	175.90
3	Application to renew an allocation notice or an approval of a dredge management plan (Act, s 83(2)(b) or 96(2)(b)), allowing the removal of—	
	(a) not more than 10000m <sup>3</sup> of quarry material . . . .	117.30
	(b) more than 10000m <sup>3</sup> of quarry material . . . . .	351.90

## **Schedule 4      Royalty payable for removal of quarry material**

section 7

\$

- |   |  |      |
|---|--|------|
| 1 | Royalty for removal of quarry material under an allocation notice or approved dredge management plan (Act, s 102(1))—for each cubic metre removed— |      |
|   | (a) by a government body or a statutory authority for its own use .....  | 0.57 |
|   | (b) otherwise .....  | 1.63 |

---

## **Schedule 4A IDAS code for development applications for prescribed tidal work**

section 16

### **Part 1 Preliminary**

#### **1 Application of code**

This code applies for the assessment of a development application for prescribed tidal work for which a local government is the assessment manager.

#### **2 Purpose of code**

The purpose of this code is to ensure prescribed tidal work for which it applies—

- (a) is compatible with the character and amenity of its surrounding area; and
- (b) is designed and constructed in a way to ensure it is structurally sound; and
- (c) is safe for use; and
- (d) is adequately serviced with infrastructure, including, for example, infrastructure for the supply of water or the discharge of sewage; and
- (e) involves only minimal use of tidal water in a canal, for a non-maritime purpose; and
- (f) does not cause a significant adverse affect to any of the following—
  - (i) existing public access to any foreshores or any tidal water;
  - (ii) navigable access to, or navigable egress from, any non-tidal work lot;

- (iii) the natural features of any tidal water, including, for example, the water quality and bed and banks of the tidal water;
- (iv) the structural integrity, operation or maintenance of any existing structure.

### 3 Definitions

In this code—

***Australian Standard*** includes a standard jointly made or published by Standards Australia and Standards New Zealand.

***axle load*** means the load applied through the axle of a vehicle.

***bed and banks***, of tidal water, means land over which the tidal water ordinarily flows or that is ordinarily covered by the tidal water, whether permanently or intermittently; but does not include adjacent land that is from time to time covered by floodwater.

***concentrated live load***, in relation to a structure, means a live load that is not uniformly distributed over the structure.

***dead load***, of prescribed tidal work, means the total load applied to the work by—

- (a) the structural components of the work; and
- (b) anything permanently on or attached to the work, including, for example, a partition or machinery permanently fixed to the work.

***distributed live load***, in relation to a structure or a part of a structure, means a live load that is uniformly distributed over the structure or the part.

***extended side boundary***, of a lot connected to prescribed tidal work, means a notional boundary worked out by extending a side boundary of the lot into tidal water—

- (a) in a continuing straight line; or
- (b) if extending the side boundary into tidal water in a continuing straight line would reduce the unimpeded

navigable access to, or egress from, an adjoining lot to less than 3m or cause a significant adverse affect to navigational safety—at an angle that ensures—

- (i) the unimpeded navigable access to, or egress from, any adjoining lot is not reduced to less than 3m; and
- (ii) no significant adverse affect is caused to navigational safety.

***factor of safety***, of a retaining wall, revetment or seawall, means the number worked out by dividing the total forces of the retaining wall, revetment or seawall that resist overturning or sliding by the total forces of the retaining wall, revetment or seawall that cause overturning or sliding.

***foreshore*** means the part of the shore between the low water mark and highest astronomical tide.

***foundation support***, for a bridge, means anything that can be used to support the bridge, including, for example, an anchor, footing or pile.

***group use***, of a structure, means use of the structure other than individual use of the structure.

***highest astronomical tide*** means the highest level of the tides that can be predicted to occur under average meteorological conditions and under any combination of astronomical conditions.

***independent deck*** means a structure that—

- (a) consists only of a deck and components to structurally support the deck; and
- (b) is not connected with another structure that is tidal work.

*Examples of a deck that is connected with another structure that is tidal work—*

- the deck of a jetty
- the deck of a pontoon

***individual use***, of a structure, means use of the structure—

- (a) that is by persons from only 1 residence, place of business or parcel of vacant land; and
- (b) that is not by a group of persons in the course of activities of an association, society, body or other entity.

*Examples of associations, societies, bodies or other entities for paragraph (b)—*

sporting or recreational club, youth group, youth organisation, scout or guide group, school or university, environmental education group

**kilonewton** means a unit of force equal to 1000 newtons.

**kN** means kilonewton.

**kPa** means kilopascal.

**lighting standard** means each of the following Australian Standards—

- (a) AS/NZS 1158.6:2004—Lighting for roads and public spaces—Luminaries;
- (b) AS/NZS 1158.3.1:1999—Road lighting—Pedestrian area (category P) lighting—Performance and installation design requirements;
- (c) AS 4282-1997—Control of the obtrusive effects of outdoor lighting.

**live load**, in relation to a structure, means the total load applied to the structure by anything temporarily on or attached to the structure.

**load** means weight, force or pressure.

**lot** includes a parcel of unallocated State land.

**major wharf** means a wharf the construction of which—

- (a) has significantly disturbed, or will significantly disturb, the substrate, flora or fauna in the locality within which the wharf is located; or
- (b) has caused, or will cause, a significant isolation of parts of land or tidal water in the locality within which the wharf is located, including, for example, the bed and banks of tidal water.

**marine plant** see the *Fisheries Act 1994*, section 8.

**minor wharf** means a wharf that is not a major wharf.

**non-private purpose** means a purpose other than a private purpose.

**non-tidal work lot** means a lot that is not, and never was, the subject of any of the following—

- (a) a development approval for prescribed tidal work;
- (b) a development approval for tidal works that are not prescribed tidal work;
- (c) a deemed approval.

**pontoon** means a structure consisting of the following components—

- (a) a flotation unit;
- (b) an access walkway for the flotation unit;
- (c) a system for mooring the flotation unit and access walkway;
- (d) an abutment.

**private boat ramp** means a boat ramp used for a private purpose.

**private slip way** means a slip way used for a private purpose.

**probable solution**, for achieving a specific outcome stated in the table, column 1, means the probable solution stated in the table, column 2 opposite the specific outcome.

**relevant engineering standard**, for prescribed tidal work, means a standard, practice, principle, procedure or other requirement accepted in the engineering industry as being an appropriate standard, practice, principle, procedure or requirement for the design or construction of work of that type.

**relevant loading matter**, for prescribed tidal work, means each of the following matters, to the extent they affect the load that can be reasonably expected to be applied to the work at any time—

- (a) the purpose or activity for which the work is intended to be used;
- (b) the dead load of the work;
- (c) the maximum number of people likely to use the work at any time;
- (d) the maximum number of vehicles likely to be on or moored at the work at any time;
- (e) the types of vehicles likely to be on or moored at the work;
- (f) the height or velocity of waves likely to occur in the tidal water under, within or over which the work is located;
- (g) any other thing that may be relevant to the load applied to the work at any time, including, for example, environmental factors.

***relevant planning scheme***, for prescribed tidal work, means the local government planning scheme applying to the lot connected to the work.

***relevant planning scheme standard***, in relation to achieving a specific outcome for prescribed tidal work, means a standard—

- (a) stated in the relevant planning scheme for the work; and
- (b) relevant to achieving the specific outcome.

***revetment*** means a wall constructed along the bottom of an embankment to—

- (a) protect the embankment from erosion; and
- (b) keep in place the materials that are landward of the wall.

***roofed*** means covered with a permanent or temporary attachment.

*Examples of temporary attachments—*

tarpaulin, umbrella, wind sail

***s 6(2) solution*** see section 5 of this code.

***seawall*** means a wall constructed along a shoreline to—



- (a) prevent the encroachment, by wave action, of the sea past the shoreline; and
- (b) keep in place the materials that are landward of the wall.

**shore abutment** means a solid wall or other structure constructed adjacent to a shoreline to counteract any force applied to the shore by a bridge, independent deck or other structure located on the shore.

**side boundary**, of a lot, means a boundary of the lot that meets tidal water but is not a waterfront boundary of the lot.

**specific outcome** means an outcome stated in the table, column 1.

**stormwater outlet** means a pipe that is the exit for an artificial passage for stormwater or floodwater.

**vegetation** does not include marine plants.

**vehicle** includes a boat or other vessel.

**waterfront boundary**, of a lot, means a boundary of the lot fronting tidal water.

#### 4 When lot connected to prescribed tidal work

For this code, a lot is connected to prescribed tidal work if—

- (a) the work is attached to the lot; or
- (b) the work is not attached to the lot but is constructed for use in association with the lot.

*Example for paragraph (b)—*

a mooring pile near, but not attached to, a lot used for mooring vessels by persons who live on the lot

#### 5 References to s 6(2) solution in probable solution

In the table, a reference to the words ‘s 6(2) solution’, in brackets, before a probable solution is a reference to the requirement, under section 6(2) of this code, that the probable solution must be complied with to achieve the specific outcome stated opposite the solution.

## Part 2 Compliance with code

### 6 How to comply with code

- (1) This code is complied with for prescribed tidal work if each specific outcome applying to the work is achieved.
- (2) A specific outcome mentioned in item 12.10, 13.1, 13.2, 15.1, 15.2, 16.1, 16.2, 16.4, 17.1, 18.1, 18.2, 18.3, 18.4, 19.1, 19.2, 19.3 or 20.1 of the table is achieved only if the probable solution for achieving the outcome is complied with.
- (3) A probable solution for achieving a specific outcome, other than a specific outcome mentioned in subsection (2), provides a guide for how the outcome may be achieved.

### 7 Relationship between particular specific outcomes and probable solutions

- (1) This section applies if there is an inconsistency or overlap between—
  - (a) a specific outcome (a *general specific outcome*) mentioned in any item in the table from item 12.1 to item 12.10, inclusive; and
  - (b) a specific outcome (a *direct specific outcome*) mentioned in any item in the table from item 13.1 to item 20.1, inclusive.
- (2) The direct specific outcome prevails to the extent of the inconsistency or overlap.
- (3) Subsection (4) applies if the probable solution for the general specific outcome includes an Australian Standard that is more stringent than a stated direct standard included in the probable solution for the direct specific outcome.
- (4) The probable solution for the direct specific outcome is taken to include the Australian Standard instead of the stated direct standard.

*Example for subsection (4)—*

An Australian Standard mentioned in the probable solution in item 12.1 of the table includes a requirement about the minimum load a boardwalk or independent deck must be able to support and the minimum load is higher than the minimum load stated, for the boardwalk or deck, in paragraph (a) of the probable solution in item 15.1 of the table. Paragraph (a) of the probable solution in item 15.1 is taken to refer to the minimum load stated in the Australian Standard.

## (5) In this section—

***stated direct standard***, included in the probable solution for a direct specific outcome, means a standard stated in the probable solution, other than a relevant planning scheme standard.

## Part 3 Specific outcomes and probable solutions

### Table

Column 1	Column 2
Specific outcome	A probable solution
<b>Character and amenity (generally)—prescribed tidal work in a canal</b>	
<p>1.1 Prescribed tidal work in a canal and for a private purpose is compatible with its location, having regard to the following—</p> <ul style="list-style-type: none"> <li>(a) the character and amenity of the work’s immediate surroundings and the locality within which the work is located;</li> <li>(b) if the relevant planning scheme states the desired character or amenity for the work’s immediate surroundings or the locality within which the work is located—the stated desired character or amenity.</li> </ul>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), prescribed tidal work does not extend past the side boundary or extended side boundary of the lot connected to the work;</li> <li>(b) subject to paragraph (c), prescribed tidal work is not roofed;</li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b);</li> <li>(d) any other relevant planning scheme standard that is not inconsistent with the standards mentioned in paragraphs (a) to (c).</li> </ul>

<b>Column 1</b>	<b>Column 2</b>
<b>Specific outcome</b>	<b>A probable solution</b>
<p>1.2 Prescribed tidal work in a canal and for a non-private purpose is compatible with its location, having regard to the following—</p> <ul style="list-style-type: none"> <li>(a) the character and amenity of the work's immediate surroundings and the locality within which the work is located;</li> <li>(b) if the relevant planning scheme states the desired character or amenity for the work's immediate surroundings or the locality within which the work is located—the stated desired character or amenity.</li> </ul>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), prescribed tidal work used for a commercial purpose does not extend past the side boundary or extended side boundary of the lot connected to the work;</li> <li>(b) subject to paragraph (c), prescribed tidal work is not roofed unless it is the main access to land;</li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard stated in paragraph (a) or (b);</li> <li>(d) any other relevant planning scheme standard that is not inconsistent with the standards mentioned in paragraphs (a) to (c).</li> </ul>

Column 1	Column 2
Specific outcome	A probable solution
<b>Character and amenity (generally)—prescribed tidal work not in a canal</b>	
<p>2.1 Prescribed tidal work not in a canal and for a private purpose is compatible with its location, having regard to the following—</p> <ul style="list-style-type: none"> <li>(a) the character and amenity of the work’s immediate surroundings and the locality within which the work is located;</li> <li>(b) if the relevant planning scheme states the desired character or amenity for the work’s immediate surroundings or the locality within which the work is located—the stated desired character or amenity.</li> </ul>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (e), prescribed tidal work does not extend past the side boundary or extended side boundary of the lot connected to the work;</li> <li>(b) subject to paragraph (e), prescribed tidal work is the only work of its type along the edge of the tidal water fronting the lot connected to the work;</li> <li>(c) subject to paragraph (e), prescribed tidal work that is a boardwalk or independent deck is not roofed;</li> <li>(d) subject to paragraph (e), prescribed tidal work other than a boardwalk or deck is not roofed unless it is the main access to land;</li> <li>(e) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a), (b), (c) or (d)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a), (b), (c) or (d);</li> <li>(f) any other relevant planning scheme standard that is not inconsistent with the standards mentioned in paragraphs (a) to (e).</li> </ul>

<b>Column 1</b>	<b>Column 2</b>
<b>Specific outcome</b>	<b>A probable solution</b>
<p>2.2 Prescribed tidal work not in a canal and for a non-private purpose is compatible with its location, having regard to the following—</p> <ul style="list-style-type: none"> <li>(a) the character and amenity of the work's immediate surroundings and the locality within which the work is located;</li> <li>(b) if the relevant planning scheme states the desired character or amenity for the work's immediate surroundings or the locality within which the work is located—the stated desired character or amenity.</li> </ul>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), prescribed tidal work used for a commercial purpose does not extend past the side boundary or extended side boundary of the lot connected to the work;</li> <li>(b) subject to paragraph (c), prescribed tidal work used for a commercial purpose is not roofed unless it is the main access to land;</li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent the standard is more stringent than the standard mentioned in paragraph (a) or (b);</li> <li>(d) any other relevant planning scheme standard that is not inconsistent with the standards mentioned in paragraphs (a) to (c).</li> </ul>

## Schedule 4A

Column 1	Column 2
Specific outcome	A probable solution
<b>Character and amenity (height, scale and size)</b>	
<p>3.1 Prescribed tidal work is of a height, scale and size to ensure the work is compatible with the character and amenity of its location, having regard to the following—</p> <ul style="list-style-type: none"> <li>(a) the height, scale and size of the natural features of the work's immediate surroundings and the locality within which the work is located;</li> <li>(b) the height, scale and size of the existing buildings or other structures in the work's immediate surroundings and the locality within which the work is located;</li> <li>(c) if the relevant planning scheme states the desired height, scale or size of buildings or other structures in the work's immediate surroundings or the locality within which the work is located—the stated desired height, scale or size.</li> </ul>	<p>The height, scale and size of the prescribed tidal work is consistent with each relevant planning scheme standard.</p>



Column 1	Column 2
Specific outcome	A probable solution
<b>Character and amenity (materials and colours)</b>	
<p>4.1 The materials used for, and the colours of, prescribed tidal work are compatible with the character and amenity of the work's location, having regard to the following—</p> <ul style="list-style-type: none"> <li>(a) the natural features of the work's immediate surroundings and the locality within which the work is located;</li> <li>(b) the existing buildings or other structures in the work's immediate surroundings and the locality within which the work is located;</li> <li>(c) if the relevant planning scheme states the desired materials to be used for, or desired colours of, buildings or other structures in the work's immediate surroundings or the locality within which the work is located—the stated desired materials or colours.</li> </ul>	<p>The materials used for, and colours of, the prescribed tidal work are consistent with each relevant planning scheme standard.</p>

Column 1	Column 2
Specific outcome	A probable solution
<b>Lighting</b>	
<p>5.1 Lighting, other than an aid to navigation, for prescribed tidal work is installed in a way to ensure the security and safe use of the work without causing significant adverse effects on the amenity of the locality within which the work is located.</p>	<p>The lighting for the prescribed tidal work, other than an aid to navigation, is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), lighting for prescribed tidal work is hooded and directed downwards;</li> <li>(b) subject to paragraph (c), each lighting standard, to the extent relevant;</li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent the standard is more stringent than the standard mentioned in paragraph (a) or (b);</li> <li>(d) any other relevant planning scheme standard that is not inconsistent with the standards mentioned in paragraphs (a) to (c).</li> </ul>

Column 1	Column 2
Specific outcome	A probable solution
<b>Signage</b>	
<p>6.1 A sign erected or otherwise placed in position for prescribed tidal work, other than a sign erected or placed for safety reasons or under an Act—</p> <ul style="list-style-type: none"> <li>(a) is compatible with the character and amenity of the work's immediate surroundings and the locality within which the work is located; and</li> <li>(b) is not a dominant feature of the work, unless the dominance is for safety reasons.</li> </ul>	<p>A sign erected or otherwise placed in position for prescribed tidal work, other than a sign erected or placed for safety reasons or under an Act, is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), a sign erected or placed in position for identifying prescribed tidal work, or the owner of the work, is the only sign erected or placed in position for identifying the work or owner;</li> <li>(b) subject to paragraph (c), a sign erected or otherwise placed in position for prescribed tidal work is integrated into the design and construction of the work;</li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a);</li> <li>(d) any other relevant planning scheme standard that is not inconsistent with the standards mentioned in paragraphs (a), (b) and (c).</li> </ul>

Column 1	Column 2
Specific outcome	A probable solution
<b>Earthwork and vegetation</b>	
<p>7.1 Excavation and filling for prescribed tidal work—</p> <ul style="list-style-type: none"> <li>(a) is carried out only to the extent reasonably necessary for the work; and</li> <li>(b) does not have a significant adverse effect on— <ul style="list-style-type: none"> <li>(i) the natural features of the tidal water under, within or over which the work is located; or</li> <li>(ii) the level of the surface of the land under the tidal water under, within or over which the work is located, or any foreshores near the work.</li> </ul> </li> </ul>	<p>The earthwork and filling for the prescribed tidal work is consistent with each relevant planning scheme standard.</p>
<p>7.2 The location of prescribed tidal work ensures vegetation is cleared or disturbed only to the extent reasonably necessary for the work.</p>	<p>The vegetation in the tidal water, under within or over which the prescribed tidal work is located, or on land under the tidal water, is cleared or disturbed in a way consistent with each relevant planning scheme standard.</p>
<p>7.3 Any vegetation damaged, destroyed or removed by prescribed tidal work under, within or over tidal water other than an artificial waterway, is replaced with appropriate vegetation.</p>	<p>Vegetation affected by the prescribed tidal work is dealt with in a way consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), vegetation damaged, destroyed or removed by prescribed tidal work is replaced with native vegetation for the locality within which the work is located, to the extent it is reasonably practicable to replace the vegetation with native vegetation;</li> </ul>

Column 1	Column 2
Specific outcome	A probable solution
	<p>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a);</p> <p>(c) any other relevant planning scheme standard that is not inconsistent with the standards mentioned in paragraphs (a) and (b).</p>
<b>Public access—availability</b>	
<p>8.1 Prescribed tidal work does not have a significant adverse effect on the availability of public access to foreshores, including public access proposed in the relevant planning scheme.</p>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <p>(a) subject to paragraph (b), prescribed tidal work does not involve the erection or placement of any physical barrier preventing existing access, along a public accessway, to the foreshores near the work;</p> <p>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a);</p> <p>(c) any other relevant planning scheme standard that is not inconsistent with the standards mentioned in paragraphs (a) and (b).</p>
<b>Public access—safety</b>	
<p>9.1 The location and design of prescribed tidal work does not adversely affect the safety of members of the public accessing the foreshores.</p>	<p>Public access to foreshores near the prescribed tidal work is consistent with each relevant planning scheme standard.</p>

Column 1	Column 2
Specific outcome	A probable solution
<b>Navigable access to, or egress from, non-tidal work lots</b>	
<p>10.1 Prescribed tidal work does not adversely affect navigable access to, or navigable egress from, any non-tidal work lot.</p>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), if the lot connected to prescribed tidal work (the <i>connected lot</i>) adjoins a non-tidal work lot, the work does not extend past the connected lot's side boundary, or extended side boundary, adjoining the non-tidal work lot;</li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>
<b>Infrastructure, including, access, parking, sewerage and water services</b>	
<p>11.1 Prescribed tidal work has appropriate infrastructure, including, in particular, road access, parking facilities, sewerage services and water services, having regard to—</p> <ul style="list-style-type: none"> <li>(a) the nature and scale of the work; and</li> <li>(b) the number of people that may be on or at the work at any time; and</li> <li>(c) the number of vehicles that may be on or moored at the work at any time; and</li> <li>(d) the protection of any foreshores near the work and the vegetation and marine plants on the foreshores.</li> </ul>	<p>The infrastructure for prescribed tidal work is consistent with each relevant planning scheme standard.</p>

Column 1	Column 2
Specific outcome	A probable solution
<b>Design, construction and safety—all prescribed tidal work</b>	
<p>12.1 Prescribed tidal work is designed and constructed in a way to ensure it is structurally sound, having regard to the following—</p> <ul style="list-style-type: none"> <li>(a) relevant engineering standards;</li> <li>(b) the location of the work;</li> <li>(c) the purpose for which the work is to be used;</li> <li>(d) the impact of flooding, tidal influences and hydrodynamic changes.</li> </ul>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), each Australian Standard relevant to the design or construction of structures, to the extent requirements stated in the Standard apply to the design or construction of prescribed tidal work;</li> <li>(b) if a relevant planning scheme standard is more stringent than any standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>
<p>12.2 Prescribed tidal work does not adversely affect the structural integrity of any existing revetment or seawall or another existing structure.</p>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), prescribed tidal work, including any shore abutment, piling or other structure connected with the work— <ul style="list-style-type: none"> <li>(i) does not place an additional load on any existing revetment or seawall or another existing structure; or</li> <li>(ii) can be structurally supported by an existing revetment or seawall or another existing structure;</li> </ul> </li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>

<b>Column 1</b>	<b>Column 2</b>
<b>Specific outcome</b>	<b>A probable solution</b>
<p>12.3 Prescribed tidal work is designed and constructed in a way to ensure it does not adversely affect the stability of the bed and banks of any tidal water.</p>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), prescribed tidal work does not cause, by changing the flow of water, the removal of, or disturbance to, the sediment on the bed and banks of any tidal water;</li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>
<p>12.4 Prescribed tidal work is designed and constructed using materials having a long life in marine environments, having regard to their ability to resist the following—</p> <ul style="list-style-type: none"> <li>(a) attack by marine organisms;</li> <li>(b) corrosion;</li> <li>(c) deterioration resulting from abrasion or immersion in seawater.</li> </ul>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), each Australian Standard relevant to the materials that should be used, or the measures that should be taken to treat materials used, for structures, to the extent the requirements stated in the Standard apply to structures located in a marine environment;</li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>



Column 1	Column 2
Specific outcome	A probable solution
<p>12.5 Prescribed tidal work is designed and constructed in a way to ensure it does not adversely affect the operation or maintenance of any existing stormwater outlet.</p>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), vessels moored at prescribed tidal work do not impede the discharge of stormwater;</li> <li>(b) subject to paragraph (c), prescribed tidal work does not restrict access to any stormwater outlet;</li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).</li> </ul>
<p>12.6 Prescribed tidal work is designed and constructed in a way to ensure it does not adversely affect the water quality of any tidal water, including, in particular, as a result of—</p> <ul style="list-style-type: none"> <li>(a) release, into the tidal water, of materials used in the construction of the work; or</li> <li>(b) disturbance to the sediment on the bed and banks of the tidal water; or</li> <li>(c) exposure to acid sulphate soils.</li> </ul>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), each Australian Standard relevant to the design or construction of structures under, within or over tidal water, to the extent the requirements stated in the Standard are directed at maintaining the water quality of tidal water;</li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>

<b>Column 1</b>	<b>Column 2</b>
<b>Specific outcome</b>	<b>A probable solution</b>
<p>12.7 Prescribed tidal work is designed and constructed in a way to ensure it is safe for persons standing or walking on the work.</p>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), any surface of prescribed tidal work on which a person may stand or walk is— <ul style="list-style-type: none"> <li>(i) not slippery; and</li> <li>(ii) does not have any feature that may cause the person to trip or fall;</li> </ul> </li> <li>(b) subject to paragraph (c), any part of prescribed tidal work that is unsafe for persons standing or walking on the work is surrounded by adequate barriers to deter persons from entering the part;</li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).</li> </ul>
<p>12.8 Appropriate measures are taken for prescribed tidal work for a non-private purpose to ensure an unsupported live load is not applied to the work by persons or vehicles.</p>	<p>The design and construction of the prescribed tidal work is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), prescribed tidal work has erected or placed in position on or near the work, a sign that— <ul style="list-style-type: none"> <li>(i) is visible at all times; and</li> <li>(ii) states the maximum live load that may be applied to the work, in terms of the maximum number of persons that may be on the work at any given time or the maximum number of vehicles of a particular type that may be on or moored at the work at any given time;</li> </ul> </li> </ul>

Column 1	Column 2
Specific outcome	A probable solution
	(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).
12.9 Prescribed tidal work, other than a boardwalk or an independent deck for a private purpose, is designed and constructed in a way that ensures the use of tidal water in a canal for a non-maritime purpose is minimised.	The design and construction of the prescribed tidal work is consistent with each relevant planning scheme standard.
12.10 Prescribed tidal work that is a boardwalk or an independent deck and for a private purpose, is designed and constructed in a way that ensures the use of tidal water in a canal for a non-maritime purpose is minimised.	(s 6(2) solution) The design and construction of the boardwalk or deck is consistent with the following standards— (a) subject to paragraph (c), a boardwalk or independent deck does not extend more than 3m from the waterfront boundary of the lot connected to the boardwalk or deck; (b) subject to paragraph (c), a boardwalk or independent deck is at least 3m inside of the side boundary or extended side boundary of the lot connected to the boardwalk or deck; (c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).

Column 1	Column 2
Specific outcome	A probable solution
<b>Design, construction and safety—boat ramps and slip ways for private purpose</b>	
<p>13.1 Prescribed tidal work that is a private boat ramp or private slip way is designed and constructed in a way to ensure it is structurally sound while also ensuring the top of each wall at the edge of the boat ramp or slip way is level with the surface of the land on which the boat ramp or slip way is located.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the boat ramp or slip way is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), the walls at the edge of a boat ramp or slip way penetrate into the earth at least 600mm below the surface of the land on which the boat ramp or slip way is located;</li> <li>(b) subject to paragraph (c), the surface of a boat ramp or slip way is no more than 200mm above the surface of the land on which it is located;</li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).</li> </ul>
<p>13.2 Prescribed tidal work that is a private boat ramp or private slip way is designed and constructed in a way to ensure the safe movement of vehicles or persons over the boat ramp or slip way.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the boat ramp or slip way is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (d), the upper surface of a boat ramp or slip way has a width of no less than 3.6m;</li> <li>(b) subject to paragraph (d), the whole upper surface of a boat ramp or slip way is treated to prevent it from becoming slippery by using any of the following methods— <ul style="list-style-type: none"> <li>(i) forming grooves over the surface, as close as possible to 40mm wide, 20mm deep and 150mm apart, and at an angle as close as possible to 70° to the centre-line of the boat ramp or slip way;</li> </ul> </li> </ul>

Column 1	Column 2
Specific outcome	A probable solution
	<ul style="list-style-type: none"> <li>(ii) covering the surface with a substance ordinarily used on slippery surfaces to prevent skidding;</li> <li>(iii) making, through a physical act, the surface coarse before it sets, including, for example, by raking the surface;</li> <li>(c) subject to paragraph (d), the upper surface of a boat ramp or slip way for which a winch is not used to hoist or haul vessels onto the boat ramp or slip way is at a gradient of not steeper than— <ul style="list-style-type: none"> <li>(i) if the surface is treated by using a method mentioned in paragraph (b)(i) or (ii)—1:8; or</li> <li>(ii) otherwise—1:10;</li> </ul> </li> <li>(d) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a), (b) or (c)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a), (b) or (c).</li> </ul>
<b>Design, construction and safety—bridges</b>	
<p>14.1 Prescribed tidal work that is a bridge does not adversely affect existing public use of any tidal water, including, for example, use of the tidal water for canoeing, swimming or other recreational activities.</p>	<p>The design and construction of the bridge, including any abutment connected with the bridge, is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), the clearance levels under a bridge are high enough to allow continued public use of any tidal water over which it is constructed;</li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>

Column 1	Column 2
Specific outcome	A probable solution
<p>14.2 Prescribed tidal work that is a bridge does not adversely affect the flow of water under the bridge.</p>	<p>The design and construction of the bridge is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b)— <ul style="list-style-type: none"> <li>(i) if a bridge can be adequately supported without erecting or placing a foundation support in tidal water—no foundation support to support the bridge is erected or placed in the tidal water; or</li> <li>(ii) otherwise—only the minimum number of foundation supports required to support the bridge is used;</li> </ul> </li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>
<b>Design, construction and safety—boardwalks and independent decks</b>	
<p>15.1 Prescribed tidal work that is a boardwalk or an independent deck and for a private purpose is designed and constructed in a way to ensure it is able to support its intended loads, having regard to its relevant loading matters.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the boardwalk or deck is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (d), a boardwalk or independent deck accessible to vehicular traffic is able to support at least a live load of 3.0kPa plus an axle load of 10kN;</li> <li>(b) subject to paragraph (d), a boardwalk or independent deck that is not accessible to vehicular traffic and that is for individual use is able to support at least a live load of 2.0kPa;</li> <li>(c) subject to paragraph (d), a boardwalk or independent deck that is not accessible to vehicular traffic and that is for group use is able to support at least a live load of 3.0kPa;</li> </ul>

Column 1	Column 2
Specific outcome	A probable solution
	(d) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a), (b) or (c)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a), (b) or (c).
<p>15.2 Prescribed tidal work that is a boardwalk or an independent deck and for a non-private purpose is designed and constructed in a way to ensure it is able to support its intended loads, having regard to its relevant loading matters.</p>	<p>(s 6(2) solution)</p> <p>The design or construction of the boardwalk or deck is consistent with the following standards—</p> <p>(a) subject to paragraph (c), a boardwalk or independent deck accessible to vehicular traffic is able to support at least the following—</p> <ul style="list-style-type: none"> <li>(i) a distributed live load of 5.0kPa;</li> <li>(ii) a concentrated live load of 4.5kN;</li> <li>(iii) the load of the largest vehicle capable of being on the boardwalk or deck;</li> </ul> <p>(b) subject to paragraph (c), a boardwalk or independent deck not accessible to vehicular traffic is able to support at least the following—</p> <ul style="list-style-type: none"> <li>(i) a distributed live load of 5.0kPa;</li> <li>(ii) a concentrated live load of 4.5kN;</li> </ul> <p>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).</p>

Column 1	Column 2
Specific outcome	A probable solution
<p>15.3 Prescribed tidal work that is a boardwalk or an independent deck does not prevent or hinder remedial work being undertaken on any bank of tidal water or for any existing retaining wall, revetment or seawall or another existing structure.</p>	<p>The design and construction of the boardwalk or deck is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), a boardwalk or independent deck either— <ul style="list-style-type: none"> <li>(i) can be easily dismantled and reassembled; or</li> <li>(ii) does not restrict the movement of machinery ordinarily used for remedial work to any bank of tidal water or any existing retaining wall, revetment or seawall or other existing structure;</li> </ul> </li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>
<b>Design, construction and safety—jetties and piers</b>	
<p>16.1 Prescribed tidal work that is a jetty or pier and for a private purpose is designed and constructed in a way to ensure it is able to support its intended loads, having regard to its relevant loading matters.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the jetty or pier is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (d), a jetty or pier accessible to vehicular traffic is able to support at least a live load of 3.0kPa plus an axle load of 10kN;</li> <li>(b) subject to paragraph (d), a jetty or pier that is not accessible to vehicular traffic and that is for individual use is able to support at least a live load of 2.0kPa;</li> <li>(c) subject to paragraph (d), a jetty or pier that is not accessible to vehicular traffic and that is for group use is able to support at least a live load of 3.0kPa;</li> </ul>



Column 1	Column 2
Specific outcome	A probable solution
	(d) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a), (b) or (c)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a), (b) or (c).
<p>16.2 Prescribed tidal work that is a jetty or pier and for a non-private purpose is designed and constructed in a way to ensure it is able to support its intended loads, having regard to its relevant loading matters.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the jetty or pier is consistent with the following standards—</p> <p>(a) subject to paragraph (c), a jetty or pier accessible to vehicular traffic is able to support at least the following—</p> <ul style="list-style-type: none"> <li>(i) a distributed live load of 5.0kPa;</li> <li>(ii) a concentrated live load of 4.5kN;</li> <li>(iii) the load of the largest vehicle capable of being on or moored at the jetty or pier;</li> </ul> <p>(b) subject to paragraph (c), a jetty or pier not accessible to vehicular traffic is able to support at least the following—</p> <ul style="list-style-type: none"> <li>(i) a distributed live load of 5.0kPa;</li> <li>(ii) a concentrated live load of 4.5kN;</li> </ul> <p>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).</p>

## Schedule 4A

<b>Column 1</b>	<b>Column 2</b>
<b>Specific outcome</b>	<b>A probable solution</b>
<p>16.3 Prescribed tidal work that is a jetty or a pier is designed and constructed in a way to ensure it remains above water at all times.</p>	<p>The design and construction of the jetty or pier is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), either— <ul style="list-style-type: none"> <li>(i) the level of the deck of a jetty or pier is at least 300mm above the water at highest astronomical tide; or</li> <li>(ii) piles or other markers indicate the presence of the jetty or pier when it is inundated;</li> </ul> </li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>
<p>16.4 Prescribed tidal work that is a jetty or pier and for a private purpose is designed and constructed in a way to ensure it is of a size suitable for maritime use while still minimising the amount of tidal water occupied by it.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the jetty or pier is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), all parts of the deck of a jetty or pier have a width of at least 900mm and not more than 3m;</li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>

Column 1	Column 2
Specific outcome	A probable solution
<b>Design, construction and safety—pipelines and other underground services</b>	
<p>17.1 The design and construction of prescribed tidal work that is a pipeline, or another underground service used instead of a pipeline, does not adversely affect the ability of vessels to be anchored near the work.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the pipeline or underground service is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), a pipeline or other underground service is installed at least 1.2m below the surface of land, after it is installed;</li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>
<b>Design, construction and safety—pontoons</b>	
<p>18.1 Prescribed tidal work that is a pontoon, for a private purpose, and not used only for rowing, is designed and constructed in a way to ensure it is able to support its intended loads, having regard to its relevant loading matters.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the pontoon is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), a pontoon for individual use is able to support at least a live load of 1.5kPa;</li> <li>(b) subject to paragraph (c), a pontoon for group use is able to support at least a live load of 2.0kPa;</li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).</li> </ul>

## Schedule 4A

Column 1	Column 2
Specific outcome	A probable solution
<p>18.2 Prescribed tidal work that is a pontoon, for a non-private purpose, and not used only for rowing, is designed and constructed in a way to ensure it is able to support its intended loads, having regard to its relevant loading matters.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the pontoon is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), a pontoon open for use by the general public or used for a commercial purpose is able to support at least the following— <ul style="list-style-type: none"> <li>(i) a distributed live load of 3.0kPa;</li> <li>(ii) a concentrated live load of 4.5kN;</li> </ul> </li> <li>(b) subject to paragraph (c), a pontoon other than a pontoon mentioned in paragraph (a) is able to support at least the following— <ul style="list-style-type: none"> <li>(i) a distributed live load of 2.0kPa;</li> <li>(ii) a concentrated live load of 4.5kN;</li> </ul> </li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).</li> </ul>

Column 1	Column 2
Specific outcome	A probable solution
<p>18.3 Prescribed tidal work that is a pontoon and used only for rowing is designed and constructed in a way to ensure—</p> <ul style="list-style-type: none"> <li>(a) it is able to support its intended loads, having regard to its relevant loading matters; and</li> <li>(b) it is safe for persons using the pontoon to launch and retrieve rowing vessels.</li> </ul>	<p>(s 6(2) solution)</p> <p>The design and construction of the pontoon is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), the access walkway of a pontoon used only for rowing is able to support at least a live load of 3.0kPa;</li> <li>(b) the flotation unit of a pontoon used only for rowing is able to support at least a live load of 1.5kPa;</li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).</li> </ul>
<p>18.4 Prescribed tidal work that is a pontoon is designed and constructed in a way to ensure any load applied to the pontoon by a person or thing on the pontoon does not cause the pontoon to tip over or tilt to a degree causing the person or thing to fall off the pontoon.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the pontoon is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (f), a pontoon's access walkway extends at least 500mm onto the pontoon's flotation unit;</li> <li>(b) subject to paragraph (f), a pontoon's access walkway is constructed with a material that has a non-slippery surface;</li> <li>(c) for a pontoon used only for rowing—subject to paragraph (f), at least 75mm of the height of the pontoon's flotation unit remains above the water over which it is constructed if a distributed live load is applied to half of the surface of the pontoon's flotation unit and all of the surface of the pontoon's access walkways;</li> </ul>

Column 1	Column 2
Specific outcome	A probable solution
	<p>(d) for a pontoon other than a pontoon mentioned in paragraph (c)—subject to paragraph (f), the top surface of the pontoon's flotation unit remains above the water over which it is constructed if a distributed live load of 1.5kPa is applied to half of the surface of the pontoon's flotation unit and all of the surface of the pontoon's access walkways;</p> <p>(e) subject to paragraph (f), the whole base of the pontoon's flotation unit remains in contact with the water over which it is constructed at all times and tilts no more than 15° at any time;</p> <p>(f) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a), (b), (c), (d) or (e)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a), (b), (c), (d) or (e).</p>
<p>18.5 Prescribed tidal work that is a pontoon is designed and constructed in a way to ensure it remains above the water at all times.</p>	<p>The design and construction of the pontoon is consistent with the following standards—</p> <p>(a) subject to paragraph (b), the pontoon's abutment is located no less than 300mm above the water at high water mark;</p> <p>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</p>

Column 1	Column 2
Specific outcome	A probable solution
<p>18.6 Prescribed tidal work that is a pontoon is designed and constructed in a way to ensure the pontoon's flotation unit will rise and fall to allow for changes in tidal water levels.</p>	<p>The design and construction of the pontoon is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) for a pontoon located in an area prone to flooding—subject to paragraph (c), the pontoon's flotation unit is moored by piles;</li> <li>(b) for a pontoon other than a pontoon mentioned in paragraph (a)—subject to paragraph (c), the pontoon's flotation unit is— <ul style="list-style-type: none"> <li>(i) attached, through the pontoon's system for mooring the unit, to concrete anchors in the bank landward of the pontoon; or</li> <li>(ii) moored by piles;</li> </ul> </li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).</li> </ul>
<b>Design, construction and safety—retaining walls, revetments and seawalls</b>	
<p>19.1 Prescribed tidal work that is a retaining wall, revetment or seawall, is designed and constructed in a way to ensure it is able to support its intended loads, having regard to its relevant loading matters.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the retaining wall, revetment or seawall is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), a retaining wall, revetment or seawall is able to support at least a distributed live load of 3.0kPa;</li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>

<b>Column 1</b>	<b>Column 2</b>
<b>Specific outcome</b>	<b>A probable solution</b>
<p>19.2 Prescribed tidal work that is a retaining wall, revetment or seawall, is designed and constructed in a way to ensure it can withstand—</p> <ul style="list-style-type: none"> <li>(a) any tendency of overturning or sliding; and</li> <li>(b) any other effects of waves or changes in water levels on the retaining wall, revetment or seawall.</li> </ul>	<p>(s 6(2) solution)</p> <p>The design and construction of the retaining wall, revetment or seawall is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), a retaining wall, revetment or seawall has a factor of safety of no less than 1.5;</li> <li>(b) subject to paragraph (c), a retaining wall, revetment or seawall is able to withstand the effect of waves, or waves and water levels, resulting from a storm or other natural event of a magnitude that has a 2% or lower probability of occurring in any calendar year;</li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).</li> </ul>



Column 1	Column 2
Specific outcome	A probable solution
<p>19.3 Prescribed tidal work that is a retaining wall, revetment or seawall not founded upon rock, is designed and constructed to protect the seaward side of retaining wall, revetment or seawall from erosion.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the retaining wall, revetment or seawall is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), a retaining wall, revetment or seawall provides for a sub-layer or enough filter material to ensure it is reasonably likely to remain in place for at least 50 years;</li> <li>(b) subject to paragraph (c), the bottom edge of the base of a retaining wall, revetment or seawall is reasonably likely to prevent any adverse effects from potential erosion of the soil under the retaining wall, revetment or seawall for at least 50 years;</li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).</li> </ul>
<p>19.4 Prescribed tidal work that is a retaining wall, revetment or seawall, is not adversely affected by hydrostatic pressure behind the retaining wall, revetment or seawall.</p>	<p>The design and construction of the retaining wall, revetment or seawall is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (b), a retaining wall, revetment or seawall provides for drainage holes, and suitable filter material behind the holes, to relieve any hydrostatic pressure behind the retaining wall, revetment or seawall;</li> <li>(b) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a).</li> </ul>

Column 1	Column 2
Specific outcome	A probable solution
<b>Design, construction and safety—wharves</b>	
<p>20.1 Prescribed tidal work that is a wharf is designed and constructed in a way to ensure it is able to support its intended loads, having regard to its relevant loading matters.</p>	<p>(s 6(2) solution)</p> <p>The design and construction of the wharf is consistent with the following standards—</p> <ul style="list-style-type: none"> <li>(a) subject to paragraph (c), a major wharf, or a minor wharf accessible to vehicular traffic, is able to support at least the following— <ul style="list-style-type: none"> <li>(i) a distributed live load of 5.0kPa;</li> <li>(ii) a concentrated live load of 13kN; or</li> </ul> </li> <li>(b) subject to paragraph (c), a minor wharf not accessible to vehicular traffic is able to support at least the following— <ul style="list-style-type: none"> <li>(i) a distributed live load of 5.0kPa; or</li> <li>(ii) a concentrated live load of 4.5kN; or</li> </ul> </li> <li>(c) if a relevant planning scheme standard is more stringent than the standard mentioned in paragraph (a) or (b)—the relevant planning scheme standard, to the extent it is more stringent than the standard mentioned in paragraph (a) or (b).</li> </ul>

---

## Schedule 5 Dictionary

## section 3

***aid to navigation*** has the meaning given by the *Transport Operations (Marine Safety) Act 1994*, section 104.

***allocation*** means an allocation of quarry material under chapter 2, part 5, division 1, of the Act.

***approved dredge management plan*** means a dredge management plan approved under section 93 of the Act.

***dredge management plan*** see section 89 of the Act.

***government body***, for schedule 4, item 1, means—

- (a) a department, or part of a department; or
- (b) a local government.

***preliminary approval*** includes a deemed approval.

***prescribed tidal work*** see section 14.

***private purpose*** means a purpose related only to either or both of the following—

- (a) use of a boat used only for recreation;
- (b) use of land, if the use is only for residential purposes.

***public marine facility*** see *Transport Infrastructure Act 1994*, schedule 6.

***residence***, for schedule 2, part 2, item 2(c), means a building or structure, or a part of a building or structure, that is used, or designed to be used, as a dwelling.

*Examples—*

- 1 dwelling house
- 2 flat or unit

***waiver application*** see section 10(1).

## Endnotes

### 1 Index to endnotes

	Page
2 Date to which amendments incorporated . . . . .	58
3 Key . . . . .	58
4 Table of reprints . . . . .	59
5 List of legislation . . . . .	59
6 List of annotations . . . . .	61

### 2 Date to which amendments incorporated

This is the reprint date mentioned in the Reprints Act 1992, section 5(c). Accordingly, this reprint includes all amendments that commenced operation on or before 18 December 2009. Future amendments of the Coastal Protection and Management Regulation 2003 may be made in accordance with this reprint under the Reprints Act 1992, section 49.

### 3 Key

#### Key to abbreviations in list of legislation and annotations

Key	Explanation	Key	Explanation
AIA	= Acts Interpretation Act 1954	(prev)	= previously
amd	= amended	proc	= proclamation
amdt	= amendment	prov	= provision
ch	= chapter	pt	= part
def	= definition	pubd	= published
div	= division	R[X]	= Reprint No. [X]
exp	= expires/expired	RA	= Reprints Act 1992
gaz	= gazette	reloc	= relocated
hdg	= heading	renum	= renumbered
ins	= inserted	rep	= repealed
lap	= lapsed	(retro)	= retrospectively
notfd	= notified	rv	= revised edition
num	= numbered	s	= section
o in c	= order in council	sch	= schedule
om	= omitted	sdiv	= subdivision
orig	= original	SIA	= Statutory Instruments Act 1992
p	= page	SIR	= Statutory Instruments Regulation 2002
para	= paragraph	SL	= subordinate legislation
prec	= preceding	sub	= substituted
pres	= present	unnum	= unnumbered
prev	= previous		

## 4 Table of reprints

Reprints are issued for both future and past effective dates. For the most up-to-date table of reprints, see the reprint with the latest effective date.

If a reprint number includes a letter of the alphabet, the reprint was released in unauthorised, electronic form only.

Reprint No.	Amendments included	Effective	Notes
1	none	20 October 2003	
1A	2003 SL No. 260	29 December 2003	
1B	2003 SL No. 269	13 January 2004	
1C	2003 SL No. 321	1 March 2004	
1D	2004 SL No. 316	17 December 2004	
1E	2005 SL No. 152	1 July 2005	
1F	2005 SL No. 275	18 November 2005	
1G	2006 SL No. 164	1 July 2006	
1H	2006 SL No. 221	28 August 2006	R1H withdrawn, see R2
2	—	28 August 2006	
2A	2007 SL No. 159	1 July 2007	
2B	2008 SL No. 207	1 July 2008	
2C	2008 SL No. 333	3 October 2008	
2D	2009 SL No. 98	1 July 2009	
2E	2009 SL No. 98	1 August 2009	R2E withdrawn, see R3
3	—	1 August 2009	
3A	2009 SL No. 280	18 December 2009	

## 5 List of legislation

### **Coastal Protection and Management Regulation 2003 SL No. 203**

made by the Governor in Council on 4 September 2003

notfd gaz 5 September 2003 pp 57–8

ss 1–2 commenced on date of notification

remaining provisions commenced 20 October 2003 (see s 2)

exp 1 September 2014 (see SIA s 54)

Notes—(1) The expiry date may have changed since this reprint was published. See the latest reprint of the SIR for any change.

(2) A regulatory impact statement and explanatory note were prepared.

amending legislation—

### **Coastal Protection and Management (Coastal Management Districts) Regulation 2003 SL No. 260 pts 1, 3**

notfd gaz 31 October 2003 pp 691–4

ss 1–2 commenced on date of notification

remaining provisions commenced 29 December 2003 (see s 2)

**Coastal Protection and Management Legislation Amendment Regulation (No. 1)  
2003 SL No. 269 pts 1, 3**

notfd gaz 7 November 2003 pp 757–60  
ss 1–2 commenced on date of notification  
remaining provisions commenced 13 January 2004 (see s 2)

**Coastal Protection and Management Legislation Amendment Regulation (No. 2)  
2003 SL No. 321 pts 1, 3**

notfd gaz 5 December 2003 pp 1114–17  
ss 1–2 commenced on date of notification  
remaining provisions commenced 1 March 2004 (see s 2)

**Environmental Protection and Other Legislation Amendment Regulation (No. 1)  
2004 SL No. 316 ss 1, 2(2), pt 2**

notfd gaz 17 December 2004 pp 1277–85  
ss 1–2 commenced on date of notification  
remaining provisions commenced 17 December 2004 (see s 2(2))

**Environmental Legislation Amendment Regulation (No. 1) 2005 SL No. 152 pts 1–2**

notfd gaz 1 July 2005 pp 763–6  
ss 1–2 commenced on date of notification  
remaining provisions commenced 1 July 2005 (see s 2)

**Coastal Protection and Management and Other Legislation Amendment Regulation  
(No. 1) 2005 SL No. 275 pts 1–2**

notfd gaz 18 November 2005 pp 1052–3  
commenced on date of notification

**Environmental Legislation Amendment Regulation (No. 1) 2006 SL No. 164 pts 1–2**

notfd gaz 30 June 2006 pp 1060–7  
ss 1–2 commenced on date of notification  
remaining provisions commenced 1 July 2006 (see s 2)

**Coastal Protection and Management Legislation Amendment Regulation (No. 1)  
2006 SL No. 221 pts 1, 3**

notfd gaz 18 August 2006 pp 1821–5  
ss 1–2 commenced on date of notification  
remaining provisions commenced 28 August 2006 (see s 2)

**Environmental Protection Legislation Amendment Regulation (No. 1) 2007 SL No.  
159 pts 1–2**

notfd gaz 29 June 2007 pp 1157–65  
ss 1–2 commenced on date of notification  
remaining provisions commenced 1 July 2007 (see s 2)

**Environmental Protection Legislation Amendment Regulation (No. 2) 2008 SL No.  
207 pts 1–2**

notfd gaz 27 June 2008 pp 1268–78  
ss 1–2 commenced on date of notification  
remaining provisions commenced 1 July 2008 (see s 2)

**Environmental Protection Legislation Amendment Regulation (No. 4) 2008 SL No. 333 pts 1–2**

notfd gaz 3 October 2008 pp 690–3  
commenced on date of notification

**Environmental Protection Legislation Amendment Regulation (No. 1) 2009 SL No. 98 pts 1–2**

notfd gaz 19 June 2009 pp 707–11  
ss 1–2 commenced on date of notification  
s 5 commenced 1 August 2009 (see s 2(2))  
remaining provisions commenced 1 July 2009 (see s 2(1))

**Sustainable Planning Regulation 2009 SL No. 280 ss 1–2, pt 9 div 6**

notfd gaz 27 November 2009 pp 1001–6  
ss 1–2 commenced on date of notification  
remaining provisions commenced 18 December 2009 (see s 2)

**6 List of annotations****Fixing coastal building lines—Act, s 66**

**prov hdg** amd 2004 SL No. 316 s 4

**s 4** amd 2003 SL No. 260 s 5

**Fees for assessment of development application**

**s 5** amd 2004 SL No. 316 s 5

**PART 3—FEES AND ROYALTIES****Division 2—Royalties****Subdivision 1—Rate of royalty and when it is payable**

**sdiv hdg** om 2004 SL No. 316 s 6

**Rate of royalty—Act, s 102**

**prov hdg** amd 2004 SL No. 316 s 7(1)

**s 7** amd 2004 SL No. 316 s 7(2)

**When royalty payable—Act, s 102**

**prov hdg** amd 2004 SL No. 316 s 7(1)

**s 8** amd 2004 SL No. 316 ss 7(2), 8

**Subdivision 2—Exemption from payment of royalty**

**sdiv hdg** om 2004 SL No. 316 s 6

**Royalty not payable for particular transport-related matters**

**prov hdg** sub 2004 SL No. 316 s 9(1)

**s 9** amd 2004 SL No. 316 s 9(2)

**Subdivision 3—Waiver of payment of royalty**

**sdiv hdg** om 2004 SL No. 316 s 6

**When waiver application may be made**

**s 11** amd 2004 SL No. 316 s 8

Endnotes

---

**PART 4—PRESCRIBED TIDAL WORK**

**pt hdg** prev pt 4 hdg om R1 (see RA s 40)  
pres pt 4 hdg ins 2005 SL No. 275 s 3

**Work that is prescribed tidal work**

**s 14** prev s 14 om R1 (see RA s 40)  
pres s 14 ins 2005 SL No. 275 s 3  
amd 2009 SL No. 280 s 62

**Work that is not prescribed tidal work**

**s 15** prev s 15 om R1 (see RA s 40)  
pres s 15 ins 2005 SL No. 275 s 3  
amd 2009 SL No. 280 s 63

**Code for IDAS for prescribed tidal work**

**s 16** prev s 16 om R1 (see RA s 40)  
pres s 16 ins 2005 SL No. 275 s 3  
amd 2009 SL No. 280 s 64

**SCHEDULE 1—COASTAL BUILDING LINES**

amd 2003 SL No. 260 s 6; 2003 SL No. 269 s 6; 2003 SL No. 321 s 6; 2004  
SL No. 216 s 10; 2006 SL No. 221 s 6

**SCHEDULE 2—FEES FOR ASSESSMENT OF DEVELOPMENT APPLICATIONS**

sub 2005 SL No. 152 s 4; 2006 SL No. 164 s 4; 2007 SL No. 159 s 4; 2008 SL  
No. 207 s 4; 2009 SL No. 98 s 4

**SCHEDULE 3—FEES FOR ALLOCATIONS AND DREDGE MANAGEMENT PLANS**

sub 2005 SL No. 152 s 4; 2006 SL No. 164 s 4; 2007 SL No. 159 s 4; 2008 SL  
No. 207 s 4; 2009 SL No. 98 s 4

**SCHEDULE 4—ROYALTY PAYABLE FOR REMOVAL OF QUARRY MATERIAL**

sub 2005 SL No. 152 s 4; 2006 SL No. 164 s 4; 2007 SL No. 159 s 4; 2008 SL  
No. 207 s 4  
amd 2008 SL No. 333 s 3  
sub 2009 SL No. 98 s 5

**SCHEDULE 4A—IDAS CODE FOR DEVELOPMENT APPLICATIONS FOR PRESCRIBED TIDAL WORK**

ins 2005 SL No. 275 s 4

**SCHEDULE 5—DICTIONARY**

def “**aid to navigation**” ins 2005 SL No. 275 s 5(1)  
def “**approved dredge management plan**” amd 2006 SL No. 221 s 7(1)  
def “**dredge management plan**” amd 2006 SL No. 221 s 7(2)  
def “**prescribed tidal work**” ins 2005 SL No. 275 s 5(1)  
def “**private purpose**” amd 2005 SL No. 275 s 5(2)  
def “**public marine facility**” amd 2005 SL No. 275 s 5(3)



© State of Queensland 2009